

COLOUR LASER PRINTER

EPSON

EPSON AcuLaser™ C3000N



more **speed** &
outstanding **colours**
for your **Business**

- 24 ppm high speed throughput for mono and colour
- Standard network & duplex printing
- 13.5 seconds first page out



*No.1 Colour Laser Printer Sales in Asia (including Japan) in 2003 & 1st Half of 2004.
Source: IDC Quarterly Printer Tracker, Q2 2004.

SPECIFICATIONS

PRINTER TYPE

PRINTING METHOD	Laser Single Pass
RESOLUTION	600dpi
PRINTING SPEED	24ppm Color & Monochrome
CPU	133 MHz

PAPER HANDLING

PAPER FEED METHOD

Standard Paper Cassette (Universal)

Capacity:	500 sheets
Paper size:	A4, A5, B5, LT, LGL, GLG, EXE
Multi-purpose Tray	
Capacity:	100 sheets
Paper size:	A4, Letter, A5, B5, HLT, EXE, LGL, GLG, F4, GLT, MON, C10, DL, C5, C6, IB5
Width:	88.9 to 215.9 mm, Length: 139.7 to 355.6 mm

1000-Sheet Paper Cassette Unit (option)

Capacity:	1,000 sheets (500 sheets x 2 cassettes)
Paper size:	A4, Letter, A5, B5, EXE, LGL, GLG

500-sheet Paper Cassette Unit (Option)

Capacity:	500 sheets
Paper size:	A4, Letter, A5, B5, EXE, LGL, GLG
Paper Eject / Capacity	Face down (maximum 250 sheets)
Duplex Printing	Standard

Paper Thickness

Weight: 60 - 216 g/m²

INTERFACES

STANDARD	High Speed USB 2.0 10/100 Base-TX Ethernet
----------	---

MEMORY

64MB (expandable to 576MB by EPSON Proprietary SDRAM DIMM)

FIRST PRINT TIME

13.5 seconds

ACOUSTIC NOISE

STAND BY:	less than 36.5dB (A)
DURING OPERATION:	less than 55dB (A)

MONTHLY PRINT VOLUME

MAXIMUM: 60,000 pages

POWER REQUIREMENTS

POWER SUPPLY / FREQUENCY

220 - 240V 10%

POWER CONSUMPTION MAXIMUM:	781 W
AVERAGE:	334 W
STANDBY MODE:	70 W
SLEEP MODE:	18 W

ENVIRONMENTAL CONDITIONS (OPERATING)

TEMPERATURE: 10 to 32°C

HUMIDITY: 15 to 85% RH

DIMENSIONS

WIDTH X DEPTH X HEIGHT: 439 X 638 X 445mm

WEIGHT: 35.5kg (including consumables)

MIN (RECOMMENDED) SYSTEM REQUIREMENT

PC	Pentium II 800MHz (Pentium III 1GHz), 256MB RAM, (512MB RAM), Free HD 500MB
MAC	PowerPC G3 233MHz (PowerPC G3 500MHz), 128MB RAM, (512MB RAM), Free HD 500MB
PC INTERFACES:	USB (Windows 98/ME/2000/XP only), 10/100 BaseTx Ethernet (optional)
MAC INTERFACES:	USB (only Macintosh systems equipped with a USB connector and running Mac OS 9.1 and above), EtherTalk (optional)
OPERATING SYSTEM:	Windows 95/98/ME/XP/2000/ Server 2003, NT 4.0, Mac OS 9.1 or later and OSX

PRINTER CONTROL LANGUAGE

STANDARD: ESC/Page-Color S (Host-based)

OPTIONS

1000-sheet paper cassette unit	C12C802071
500-sheet paper cassette unit	C12C802061

CONSUMABLES

3.5K Capacity Toner Cartridge (Yellow)	C13S050210
3.5K Capacity Toner Cartridge (Magenta)	C13S050211
3.5K Capacity Toner Cartridge (Cyan)	C13S050212
4.5K Capacity Toner Cartridge (Black)	C13S050213
Photoconductor Unit	C13S051093
Fuser Unit	C13S053012
Transfer Unit	C13S053006

COLOUR LASER EPSON AcuLaser™ C3000N



PostScript is a trademark of Adobe Systems Incorporated or its subsidiaries and may be registered in certain jurisdictions.
All other product names and other company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners.
EPSON disclaims any and all rights for those marks.
Specifications are subject to change without notice.

EPSON

For enquiries, contact your nearest EPSON sales representatives :



see our:



www.epson.com.sg