

PRINTER TYPE	PRINTING METHOD	Impact dot matrix	
	PRINT DIRECTION	<ul style="list-style-type: none"> • Bi-directional with logic seeking in text mode. (Unidirectional printing can be selected by software) • Unidirectional in bit image and graphic modes 	
	INPUT DATA BUFFER	20k byte or 0k byte (selectable)	
CONSUMABLES	RIBBON CARTRIDGE BLACK	Fabric Ribbon Cartridge 15 million characters (14 dots per character)	#8766
DIMENSIONS	WIDTH x DEPTH x HEIGHT	700 x 382 x 369mm	
	WEIGHT	29kg	
PRINT SPEED		<ul style="list-style-type: none"> • High Speed Draft 10 cpi • Draft 10 cpi • NLQ 10 cp 	560 cps 420 cps 84 cps
RELIABILITY	MTBF (Mean Print Volume Between Failure)	8,000 POH	
	PRINT HEAD LIFE	300 million characters (14 dots per character)	
BUILT-IN FUNCTIONS		<ul style="list-style-type: none"> • Automatic tear-off • Automatic I/F selection • Paper-Jam detection • Automatic paper thickness adjustment • Binding skip • Paper-width detection • Paper memory function • Hex dump • Self test printing; Draft/NLQ • Input data buffering • Buffer-full printing • Paper-out detection • Case-open detection 	
PRINT CHARACTERISTICS	CHARACTER SETS	<ul style="list-style-type: none"> • 13 international character sets • 9 character tables • 2 character tables (IBM mode) 	
	FONTS	<ul style="list-style-type: none"> • EPSON Roman 10, 12, Condensed 17.1, 20 • EPSON Sans serif 10, 12, Condensed 17.1, 20 • EPSON Draft 10, 12, Condensed 17.1, 20 	
PRINTABLE COLUMNS	CHARACTERS SIZE (MM)	<ul style="list-style-type: none"> • cpi 2.12 x 3.1 • cpi Condensed 1.06 x 3.1 • cpi Condensed 1.69 x 3.1 • cpi Condensed 0.85 x 3.1 	
	CHARACTER PER LINE	<ul style="list-style-type: none"> • cpi 136 • cpi Condensed 233 • cpi Condensed 163 • cpi Condensed 272 	
	CHARACTERS PER INCH	<ul style="list-style-type: none"> • cpi 10 • cpi Condensed 17.1 • cpi Condensed 12 • cpi Condensed 20 	
CONTROL PANEL	SWITCHES	<ul style="list-style-type: none"> • Pause • LF/FF Load • Tear off • Micro feed • Top of form • Pitch • Paper select front/rear 	
INTERFACE	STANDARD	<ul style="list-style-type: none"> • Centronics® -type 8-bits parallel interface • RS-232C serial interface 	
	OPTIONAL	Type B interface (see OPTIONS)	
PAPER HANDLING	PAPER PATH	Front/Rear	
	CONTINUOUS PAPER SIZE	Width: 101mm - 406mm	
	PAPER THICKNESS	0.46mm max. Front, 0.30mm max. Rear	
	COPIES	1 + 5 Front, 1 + 3 Rear	
	LINE SPACING	1/8" or 1/8" or programmable (min.1/216")	
	PAPER FEEDING	Push Tractor Feed, Push-Pull Feed (with optional pull tractor)	
OPTIONS		<ul style="list-style-type: none"> • Pull-Tractor Unit • Serial Interface Card • 32KB Intelligent Serial Interface Card • 32KB Intelligent Parallel Interface Card • Interface Card for LocalTalk™ • 32KB IEEE-488 Interface Card • Co-ax Interface Card • Twin-ax Interface Card • Ethernet Interface Card for NetWare® 	#8309 C823061 C823081 C823102 C823122 C823132 C823142 C823152 C823242
POWER REQUIREMENTS	VOLTAGE	120V AC, 220/240V AC	
	RATED FREQUENCY	49.5 - 60.5Hz	
	POWER CONSUMPTION	<ul style="list-style-type: none"> • Approx. 115W (120V) • Approx. 110W (220/240V) 	
ENVIRONMENTAL CONDITIONS	TEMPERATURE	5 - 35° C	
	HUMIDITY	10% - 80% RH	