

SPECIFICATIONS

EPSON
EXCEED YOUR VISION

Weight – approx. 5.7lbs. / 2.6kg




PROJECTION DISTANCE

| Diagonal Screen Size (inches) | Wide (cm) | Tele (cm) |
|-------------------------------|-----------|-----------|
| 30 | 87 | 119 |
| 40 | 117 | 159 |
| 60 | 177 | 240 |
| 80 | 237 | 321 |
| 100 | 297 | 402 |
| 200 | 597 | 807 |
| 300 | 897 | 1212 |

Multimedia Projector EMP-S4

| | | | |
|--|--|---|--|
| PART NUMBER | V11H221052 | | |
| PROJECTION SYSTEM | RGB Liquid-Crystal Shutter Projection System | | |
| SPECIFICATION OF MAIN PARTS | LCD | SIZE DRIVING METHOD PIXEL NUMBER NATIVE RESOLUTION | 0.5 inch with MLA (x 3) Polysilicon TFT Active Matrix 480,000 dots (800 x 600) x 3 SVGA |
| | PROJECTION LENS | | Manual Focus & 1.35 x Digital Zoom F=1.4 / f=16.6 mm |
| | LAMP | TYPE LIFE* | 170 W UHE 2000 hours (High Brightness Mode) / 3000 hours (Low Brightness Mode) |
| *These are not the guaranteed number of lamp hours, but the recommended hours after which the lamp should be replaced in order to ensure optimum picture quality | | | |
| SCREEN SIZE (PROJECTED DISTANCE) | 30 to 300 inch (0.9 to 12.1 m) | | |
| BRIGHTNESS | HIGH / LOW BRIGHTNESS MODE | 1800 ANSI lm / 1500 ANSI lm | |
| CONTRAST | 500:1 | | |
| BRIGHTNESS UNIFORMITY | 85% | | |
| COLOUR REPRODUCTION | Full-Colour (16.77 million colours) | | |
| SOUND OUTPUT | 1 W Monaural | | |
| EFFECTIVE SCANNING FREQUENCY RANGE (ANALOG) | PIXEL CLOCK HORIZONTAL VERTICAL | 13.5 MHz to 162 MHz 15 kHz to 92 kHz 50 Hz to 85 Hz | |
| KEystone CORRECTION | Vertical: -30 to +30 degrees | | |
| ANALOG RGB I/O | DISPLAY PERFORMANCE INPUT TERMINAL OUTPUT TERMINAL | NATIVE RESIZE VIDEO AUDIO VIDEO | 800 x 600 dots 1280 x 1024 / 1024 x 768 / 640 x 480 D-sub 15-pin x 1 RCA x 2 D-sub 15-pin x 1 |
| VIDEO I/O | INPUT SIGNAL INPUT TERMINAL AUDIO | VIDEO STANDARD VIDEO | NTSC / NTSC4.43 / PAL / M-PAL / N-PAL / PAL60 / SECAM Composite Video: RCA (Yellow) x 1 S-Video: Mini DIN x 1 Component Video: D-sub 15-pin x 1 Video-RGB: D-sub 15-pin x 1 RCA x 2 |
| CONTROL I/O | USB I/O TERMINAL | Type B x 1 | |
| OPERATING TEMPERATURE | 5°C to 35°C <41°F to 95°F> | | |
| START-UP PERIOD | About 4 Sec. | | |
| COOL-DOWN PERIOD | Instant Off | | |
| POWER SUPPLY VOLTAGE | 100 - 240 VAC ±10% , 50 / 60 Hz | | |
| POWER CONSUMPTION | Lamp On Stand-by | 240W 6W | |
| DIMENSIONS (D X W X H) | 247 x 327 x 87 mm (Excludes Feet) | | |
| WEIGHT | Approx. 5.7 lbs. / 2.6 kg | | |
| FAN NOISE | 30 dB (Low Brightness Mode) | | |
| SUPPLIED ACCESSORIES | Power Cable Computer Cable Remote Control Soft Carrying Case Password Protect Sticker User's Manual | | |
| | | 1.8 m 1.8 m With AAA Type Alkaline Batteries x 2pcs | |
| OPTIONAL ACCESSORIES | ELPLP36 (Part No. V13H010L36) ELPAF08 (Part No. V13H134A08) | | |
| | | Replacement Lamp Air Filter Set, 2 Sheets | |

CONNECTOR PANEL



EPSON
EXCEED YOUR VISION

1 Harbourfront Place
#03-02 HarbourFront Tower One
Singapore 098633

(65) 6586 5500
(65) 6334 2710

Dealer's Stamp

www.epson.com.sg

Multimedia Projector EMP-S4



**Style, Value
and Versatility**



- High Luminance of 1800 ANSI lm With SVGA Resolution
- Unique A/V Mute Slide Function
- Quick Start-up And "Instant Off" Shutdown

ENJOY VERSATILITY, VALUE & OUTSTANDING PERFORMANCE

Multimedia Projector EMP-S4



Make a lasting impression with Epson's latest projector, the EMP-S4. With stylish enhancements and innovative features, you can now impress your audience with sleeker presentations, and enjoy greater home entertainment.

Bold, Bright & Beautiful With 3LCD Technology



3LCD Projector



1-chip DLP™ Projector

1-chip DLP™ (Digital Light Processing™) is a trademark of Texas Instruments Incorporated.

Epson's 3LCD technology enables you to enjoy smoother, sharper video playback with more vibrant, natural images. Images are clearer and easier on the eye without any dither noise or colour break-up common in the other projector technology in the market.

Fuss-Free Buttons



Whether you are a beginner or an expert, using the EMP-S4 is a breeze with Epson's user-friendly operation panel. Large, clear buttons eliminate confusion and give you easy control at your fingertips.

Innovative E-TORL Lamp



E-TORL



(E-TORL : Epson-Twin Optimize Reflection Lamp)

Epson's innovative E-TORL lamp system eliminates light leakage and minimises light defraction, giving you superior resolution and image quality.

The system combines an ellipsoidal reflector with an aspherical lens and a hemispherical mirror to produce a lamp that is as small as it is efficient.

Easy-To-Use Help Function

Troubleshoot your problems swiftly with Epson's step-by-step onscreen guide. The simple question and answer format will get you back to your presentation fast – with minimal disruption!

Source Search

The source search feature automatically detects the picture signal with the press of a button, connecting the picture seamlessly.

Direct Power-On & Quick Start-Up

The Direct Power-On function means the EMP-S4 is activated automatically when the power plug is connected. Combined with the 4-second start-up time, these additional features get your presentation up and running in a flash.

Security Functions

Power-On Protect / User's Logo Protect / Timer Protect / Key Lock

To minimise unauthorised usage, Epson's 3 password protected functions ensure your presentations are safe with a password only you have access to. The operational key lock feature also secures the control panel buttons* to avoid accidental tampering of your settings, giving you complete peace of mind.

*Except for the Power button

Hassle-Free Pack-And-Go Versatility



Enjoy optimised mobility with Epson's "Instant Off" feature. No cool-down time is required with EMP-S4 immediate shutdown. Simply hit the power button and unplug the power cable after your presentation. Saves you valuable time!

A/V Mute Slide – For Smoother Presentations



Close Slide, A/V Mute



Open Slide

Simply slide the A/V mute cover across and the EMP-S4 allows you to pause projection temporarily. The audience can then focus on you, or other elements of your presentation.

Fan noise is minimised when the slide is closed, while the projector light is suspended temporarily – allowing you to take advantage of the white board without distracting your audience.

7 Colour Modes

The EMP-S4 offers 7 preset projection modes to suit your specific needs, allowing you to choose the optimum colour mode for your environment.

sRGB – Suits images that conform to the sRGB colour standard

Presentation – Ideal for giving presentations in a brightly lit room

Blackboard – This setting gives your images a natural tone by removing the green tint

Photo – Ideal for projecting still pictures and photos in a brightly lit room

Sports – Great for bringing to life component video, S-video, or composite video images

Theatre – Ideal for watching films in a darkened room

Game – This setting minimises glare when the projector is used in a brightly lit room

