

MONOCHROME LASER PRINTER

EPSON

# EPSON EPL-6200

The Affordable  
*Networking* Printer  
For Your Business

- ✓ Fast print speed of 20 ppm
- ✓ Less than 13 seconds first page out
- ✓ True 600 dpi resolution
- ✓ 8MB Memory
- ✓ Powerful 200MHz processor
- ✓ Standard Adobe® PostScript® 3™



## PRINTER TYPE

<b>PRINTING METHOD</b>	Electrophotography + Laser
<b>RESOLUTION</b>	300dpi, 600dpi, 1200dpi
<b>PRINTING SPEED</b>	Mono 20ppm(A4 at 600dpi X 600dpi) Mono 10ppm(A4 at 1200dpi X 1200dpi)
<b>CPU</b>	200MHz

## PAPER HANDLING

### PAPER FEED METHOD

#### Standard Paper Cassette

Capacity:	250 sheets
Paper size:	A4, A5, B5, LT, HLT, LGL, EXE, GLG, GLT, F4
Envelope:	Mon, C10, DL, C5, C6, IB5
Transparencies:	A4, LT
Label:	A4, LT

#### 500-Sheet Lower Paper Cassette Unit A4(Optional)

Capacity:	500 sheets
Output Capacity:	100 sheets
<b>Paper Eject / Capacity</b>	
Face down:	(Maximum 100 sheets)
<b>Paper Thickness</b>	
Weight:	60 - 163 g/m <sup>2</sup>

## DUPLEX PRINTING

Option \*1

## INTERFACES

<b>STANDARD</b>	IEEE1284 compatibility parallel interface 1 slot for Type B interface card USB 1.1 interface
-----------------	--

## PRINTER CONTROL LANGUAGE

<b>STANDARD</b>	Adobe® Postscript® 3™, ESC/Page, ESC/P2, PCL6, PCL5e, FX, IBM Mode(I239X), EPSON GL2
-----------------	--

## MEMORY

8 MB (Expandable to 136MB)

## WARM-UP TIME

21 seconds or less (From power on)  
16 seconds or less (From Sleep mode)

## FIRST PRINT TIME

Less than 13 seconds (Standard MP tray A4)

## ACOUSTIC NOISE

<b>STAND BY:</b>	39dB Ave.
<b>DURING OPERATOR:</b>	54dB Ave.

## DURABILITY

5 years or 180,000 pages whichever comes first

## MONTHLY PRINT VOLUME

<b>MAXIMUM:</b>	15,000 pages
<b>AVERAGE:</b>	2,500 pages

## POWER REQUIREMENTS

<b>POWER SUPPLY / FREQUENCY:</b>	220V - 240V ±10%
<b>POWER CONSUMPTION 220V - 240V</b>	<b>MAXIMUM:</b> 861 W
	<b>OPERATION:</b> 372 Wh Ave.
	<b>STANDBY MODE:</b> 48 Wh Ave.
	<b>SLEEP MODE:</b> 7 Wh Ave.

## ENVIRONMENTAL CONDITIONS (OPERATING)

<b>TEMPERATURE:</b>	10 to 35°C
<b>HUMIDITY:</b>	15 to 85% RH

## DIMENSIONS

<b>WIDTH X DEPTH X HEIGHT:</b>	407 X 436 X 261mm
<b>Weight:</b>	7kg (excluding consumables)

## PRINTER DRIVER/UTILITY

**PRINTER DRIVER FOR:** Microsoft® Windows® 95/98/ME/2000/ XP, Windows NT™ version 4.0, Mac™ OS 8.6 or later, Mac™ OS X 10.1.2 or later

**EPSON STATUS MONITOR 3 FOR:** Microsoft® Windows® 95/98/ ME/2000/XP, Windows NT™ version 4.0, Mac™ OS 8.6 or later, Mac™ OS X 10.1.2 or later

**EPSON FONT MANAGER FOR:** Microsoft® Windows® 95/98/ ME/2000/XP, Windows NT™ version 4.0

**BAR CODE FONTS FOR:** Microsoft® Windows® 95/98/ ME/2000/XP, Windows NT™ version 4.0

**POSTSCRIPT® PRINTER DRIVER FOR:** Microsoft® Windows® 95/98/ ME/2000/XP, Windows NT™ version 4.0, Mac™ OS 8.6 or later, Mac™ OS X 10.2.4 or later

## SYSTEM REQUIREMENTS

### WINDOWS ENVIRONMENT

#### Minimum requirements

<b>CPU:</b>	Pentium
<b>Clock:</b>	133MHz
<b>Memory:</b>	16 MB
<b>Interface:</b>	IEEE 1284 Parallel Standard USB (optional USB board is not supported) *Windows 95 is not supported with USB
<b>OS:</b>	Windows 95/98/Me/XP/2000/NT4.0

#### Recommended requirements

<b>CPU:</b>	Pentium
<b>Clock:</b>	233 MHz
<b>Memory:</b>	64 MB
<b>Interface:</b>	IEEE 1284 Parallel Standard USB (optional USB board is not supported) *Windows 95 is not supported with USB
<b>OS:</b>	Windows 95/98/Me/XP/2000/NT4.0

### MAC ENVIRONMENT

#### Minimum requirements

<b>CPU:</b>	Power MacG3 with standard USB or iMac,iBook
<b>Clock:</b>	233 MHz
<b>Memory:</b>	32 MB
<b>Interface:</b>	Standard USB (optional USB board is not supported)
<b>OS:</b>	Mac OS 8.6 or 9.x or X 10.1.2

#### Recommended requirements

<b>CPU:</b>	Power MacG3 with standard USB or iMac,iBook
<b>Clock:</b>	233 MHz
<b>Memory:</b>	64 MB
<b>Interface:</b>	Standard USB (optional USB board is not supported)
<b>OS:</b>	Mac OS 8.6 or 9.x or X 10.1.2

## CONSUMABLES

Developer Cartridge	Lifespan:	3,000 pages*2	C13S050167
Developer Cartridge	Lifespan:	6,000 pages*2	C13S050166
Photoconductor Unit	Lifespan:	20,000 pages*2	C13S051099

## OPTIONS

500-Sheet Lower Paper Cassette Unit A4	C12C802042
Duplex Unit	C12C802051

\*1 The optional Duplex Unit can be installed only if the optional 500-sheet Lower Paper Cassette Unit A4 is already attached to the printer.

\*2 Approximate number of sheets under conditions of continuous printing on A4/letter size paper with 5 percent page coverage.

## LASER PRINTER EPSON EPL-6200



\*EPSON ESC/P2 stands for EPSON standard code for printers. This second generation printer control language supports scalable fonts as well as enhanced graphics capability.

It also provides complete backwards compatibility with EPSON's ESC/P, the standard printer language for dot matrix printing. EPSON is a registered trademark of SEIKO EPSON CORPORATION. EPSON ESC/P2 is a trademark of SEIKO EPSON CORPORATION. PostScript is a trademark of Adobe Systems Incorporated or its subsidiaries and may be registered in certain jurisdictions. All other product names and other company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. EPSON disclaims any and all rights for those marks. Specifications are subject to change without notice.

Dealer's stamp

# EPSON

For enquiries, contact your nearest EPSON sales representatives :

INDIA - (91) 80-532 1266-70, CALCUTTA - 287 1355/56, CHENNAI - 820 3941/42, MUMBAI - 825 7286, NEW DELHI - 644 7201/2/3  
INDONESIA - (62) 21-572 3161 MALAYSIA - (60) 03-562-88288 PHILIPPINES - (632) 813-6567  
SINGAPORE - (65) 6472 2822 THAILAND/INDOCHINA - (66) 2670 0680

www.epson.com.sg