

EPSON EPL-N2500

because

Asia
Business

demands

Diversity
&
Versatility

- ✓ Fast print speed of 25 ppm (A4) & 15 ppm (A3)
- ✓ Less than 8.2 seconds first page out
- ✓ 16MB memory (Max. 144MB)
- ✓ Parallel, USB & Type B interface
- ✓ Duplex & network options



PRINTER TYPE

PRINTING METHOD	Electrophotography + Laser
RESOLUTION	600dpi
PRINTING SPEED	Mono 25ppm(A4 at 600dpi X 600dpi) Mono 15ppm(A3 at 600dpi X 600dpi)
CPU	200MHz

PAPER HANDLING

PAPER FEED METHOD

Standard Paper Cassette

Capacity:	250 sheets
Paper size:	A3, A4, A5, B4, B5, IT, HLT, IGL, EXE, CLG, GLT, F4
Envelope:	Mon, C10, DL, C5, C6, IB5
Transparencies:	A4, LT
Label:	A4, LT

500-Sheet Lower Paper Cassette Unit A4(Option)

Capacity:	550 sheets
Output Capacity:	250 sheets
Paper Eject / Capacity	
Face down:	(Maximum 250 sheets)
Paper Thickness	
Weight:	60 - 216 g/m ²

DUPLEX PRINTING

Option

INTERFACES

STANDARD	IEEE1284 compatibility parallel interface 1 slot for Type B interface card USB 1.1 interface
-----------------	--

PRINTER CONTROL LANGUAGE

STANDARD	ESC/Page, ESC/P2, PCL5e, FX, IBM Mode(I239X), EPSON GL2
-----------------	--

MEMORY

16 MB (Expandable to 144MB)

WARM-UP TIME

12 seconds or less (From power on)
10 seconds or less (From Sleep mode)

FIRST PRINT TIME

Less than 5.2 seconds (Standard MP tray A4)

ACOUSTIC NOISE

STAND BY:	33dB Ave.
DURING OPERATON:	53dB Ave.

DURABILITY

5 years or 600,000 pages whichever comes first

MONTHLY PRINT VOLUME

MAXIMUM:	75,000 pages
AVERAGE:	10,000 pages

POWER REQUIREMENTS

POWER SUPPLY / FREQUENCY:	220V - 240V ±10%
POWER CONSUMPTION 220V - 240V	MAXIMUM: 920 W
	OPERATION: 578 Wh Ave.
	STANDBY MODE: 119 Wh Ave.
	SLEEP MODE: 5 Wh Ave.

ENVIRONMENTAL CONDITIONS (OPERATING)

TEMPERATURE:	10 to 35°C
HUMIDITY:	15 to 80% RH

DIMENSIONS

WIDTH X DEPTH X HEIGHT:	513 X 395 X 324mm
Weight:	19.5kg (excluding consumables)

PRINTER DRIVER/UTILITY

PRINTER DRIVER FOR:	Microsoft® Windows® 95/98/ME/2000/ XP, Windows NT™ version 4.0, Mac™ OS 8.6 or later
----------------------------	--

EPSON STATUS MONITOR 3 FOR:	Microsoft® Windows® 95/98/ ME/2000/XP, Windows NT™ version 4.0, Mac™ OS 8.6 or later
------------------------------------	--

EPSON FONT MANAGER FOR:	Microsoft® Windows® 95/98/ ME/2000/XP, Windows NT™ version 4.0
--------------------------------	---

BAR CODE FONTS FOR:	Microsoft® Windows® 95/98/ ME/2000/XP, Windows NT™ version 4.0
----------------------------	---

SYSTEM REQUIREMENTS

WINDOWS ENVIRONMENT

Minimum requirements

CPU:	Pentium
Clock:	133MHz
Memory:	16 MB
Interface:	IEEE 1284 Parallel Standard USB (optional USB board is not supported) *Windows 95 is not supported with USB
OS:	Windows 95/98/Me/XP/2000/NT4.0

Recommended requirements

CPU:	Pentium
Clock:	233 MHz
Memory:	64 MB
Interface:	IEEE 1284 Parallel USB (optional USB board is not supported) *Windows 95 is not supported with USB
OS:	Windows 95/98/Me/XP/2000/NT4.0

MAC ENVIRONMENT

Minimum requirements

CPU:	Power MacG3 with standard USB or iMac,iBook
Clock:	233 MHz
Memory:	32 MB
Interface:	Standard USB (optional USB board is not supported)
OS:	Mac OS 8.6 or 9.x

Recommended requirements

CPU:	Power MacG3 with standard USB or iMac,iBook
Clock:	233 MHz
Memory:	64 MB
Interface:	Standard USB (optional USB board is not supported)
OS:	Mac OS 8.6 or 9.x

CONSUMABLES

Imaging Cartridge	Lifespan: 10,000 pages*1	C13S051091
-------------------	--------------------------	------------

OPTIONS

500-Sheet Lower Paper Cassette Unit A4	C12C802002
Duplex Unit	C12C813982
PS In-house Installation Kit	C12C832561
Ethernet 10/100 BaseT Internal Print Server	C12C823914

*1 Approximate number of sheets under conditions of continuous printing on A4/letter size paper with 5 percent page coverage.

MONOCHROME LASER PRINTER EPSON EPL-N2500



*EPSON ESC/P2 stands for EPSON standard code for printers. This second generation printer control language supports scalable fonts as well as enhanced graphics capability.

It also provides complete backwards compatibility with EPSON's ESC/P, the standard printer language for dot matrix printing. EPSON is a registered trademark of SEIKO EPSON CORPORATION. EPSON ESC/P2 is a trademark of SEIKO EPSON CORPORATION. PostScript is a trademark of Adobe Systems Incorporated or its subsidiaries and may be registered in certain jurisdictions. All other product names and other company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. EPSON disclaims any and all rights for those marks. Specifications are subject to change without notice.

Dealer's stamp

EPSON

For enquiries, contact your nearest EPSON sales representatives :

INDIA - (91) 80-532 1266-70, CALCUTTA - 287 1355/56, CHENNAI - 820 3941/42, MUMBAI - 825 7286, NEW DELHI - 644 7201/2/3
INDONESIA - (62) 21-572 3161 MALAYSIA - (60) 03-562-88288 PHILIPPINES - (632) 813-6567
SINGAPORE - (65) 6472 2822 THAILAND/INDOCHINA - (66) 2670 0680

www.epson.com.sg