EESOLUTION  640 X 48    PIXEL DENSITY  212ppi    UNMERG OF DOTS  640 X 3 (    HARD DISK DRIVE  640 X 3 (    SIZE  40GB 2.5    SUPPORTED MEDIA	RGB) X 480 = 921,600 pixe			Mul	
HESOLUTION  640 X 48    VIXEL DENSITY  212ppi    UNMBER OF DOTS  640 X 3 (    HARD DISK DRIVE  640 X 3 (    SIZE  40GB 2.5    SUPPORTED MEDIA	0 (VGA) RGB) X 480 = 921,600 pixe 5" (3.5GB reserved for syst AW <sup>23</sup> Simple Profile)			Mul	
HXEL DENSITY  212ppi    VLMEER OF DOTS  640 X 3 (    HARD DISK DRIVE  3000 B 2.5    SIZE  40GB 2.6    UPPORTED MEDIA  2000 B 2.5    PHOTOS  JPEG <sup>1</sup> , R    MOVIES  MPEG-41	RGB) X 480 = 921,600 pixe (3.5GB reserved for syst AW <sup>23</sup> Simple Profile)			Mu	
AVAILABLE OF DOTS 640 X 3 ( HARD DISK DRIVE SIZE 40GB 2.5 SUPPORTED MEDIA HOTOS JPEG <sup>1</sup> , R MOVIES MPEG <sup>4</sup> , Approx.3	i" (3.5GB reserved for syst AW <sup>23</sup> Simple Profile)				
SIZE 40GB 2.E SUPPORTED MEDIA "HOTOS JPEG <sup>1</sup> , R MOVIES MPEG <sup>4</sup> , Approx.3	AW <sup>23</sup> Simple Profile)	tem functions)			
SUPPORTED MEDIA PHOTOS JPEG <sup>1</sup> , R MOVIES MPEG-4( Approx.3	AW <sup>23</sup> Simple Profile)	tem functions)			
HOTOS JPEG <sup>1</sup> , R MOVIES MPEG-4( Approx.3	Simple Profile)				
MOVIES MPEG-40 Approx.3	Simple Profile)				
Approx.3			JPEG <sup>1</sup> , RAW <sup>23</sup>		
	0 Mbps(Max)/2 5 Mbps(A)				
		ve.), 30fps, VGA Mot	ion JPEG Approx.		
3Mbps, 3 MUSIC MP3 <sup>4</sup> . Ar	80fps, VGA				
MUSIC MP3*, A/	AC*				
	wing file types are support		hoto!4 v1.8 (included)		
	AVI, .MOV, .MPG, .MP4 File Format supported <sup>5</sup> Video: DV, MotionJPG, Cinepac, MPEG-1, MPEG-2 <sup>6</sup> , MPEG-4 <sup>7</sup>				
	Law, µLaw, PCM, AAC, MI le format: MPEG-4 AAC (.r				
	ze: 640 X 480, Bit rate: 2M		ps,		
	Flash® (I&II), SD Memory				
*Other c	ards supported via Compac	ct Flash adapter (not i	included)		
AUDIO AND VIDEO OUT Mono dy	namic speaker				
Stereo 3	5mm headphone jack				
Audio/Vio	leo out jack				
PAL and	NTSC supported				
NTERFACE USB 2.0	Hi-Speed for PC and Mac o	connection			
POWER					
	able Li-Ion battery, 3.7V, 2				
	in continuous slide show	mode			
EXTERNAL POWER DC INPU	T 5V 2.3A				
RECOMMENDED MINIMUM SYSTEM REQUIRE	CPU	RAM	FREE HARD DISK SPACE		
	um 1GBHz or higher	128MB or more	50MB or more		
	um 1GBHz or higher	128MB or more	50MB or more		
	um 1GBHz or higher	128MB or more	50MB or more		
	um 1GBHz or higher	128MB or more	50MB or more		
	C G3 233MHz or higher	128MB or more	50MB or more		
	C G3 700MHz or higher applications and/or function	256MB or more as will not be support	50MB or more ed under Mac OS X		
	er, power cable, Lithium-lo , USB cable, strap, carrying		ual, software		

## 2000 nedia Storage Viewer



Weight 415g

## **P-2000**



Multimedia Storage Viewer



## Moments of Beauty - All in your Hands

Superb EPSON Photo Fine Solution On-the-Move

**TOP** ACHAT

REPONSES PHOTO

2004 1

www.epson.com.sg www.epsonphoto.com.sg

**EPSON** 

Maximum Image Size: 17.8 MegaPixels <sup>2</sup> JPEG within RAW file header is used for display

6 Requires QuickTime MPEG-2 plug-in component

<sup>5</sup> Input data which is supported by Photo14 is based on OuickTime spec

<sup>7</sup> Only MPEG4 files with a resolution greater than VGA are resized to VGA

4 320kbps max bit rate

<sup>3</sup> Supports Nikon D100 / D1H / D2H / D1X / D70, Canon EOS 300D / D60 / D30/10D /20D/ 1D Mark II/ 1Ds Mark II, KonicaMinolta Dynax 7D and Pentax ist\*DS/ ist\*D

