

## EPSON STYLUS<sub>IM</sub> PRO 4400



SIZE 17 inch wide (A2+)

**PRINTER TYPE** 

PRINTING METHOD On-demand ink jet (piezoelectric)

NOZZLE CONFIGURATION 180 nozzles x 8

**PRINT QUALITY** 

MAXIMUM RESOLUTION 1440 x 720 dpi with EPSON Variable Sized Droplet Technology (VSDT)

**INK SYSTEM** Epson UltraChrome Ink (Individual 4 colour high capacity ink cartridge in

110ml or 220ml) Matte Black, Cyan, Magenta, Yellow

**PRINTER SPEED** A2 size, Colour

360 dpi x 360 dpi : Approx. 0.9 mins (Plain paper : Draft mode) 360 dpi x 360 dpi : Approx. 1.3 mins (Plain paper : Fast mode) 720 dpi x 360 dpi : Approx. 2.3 mins (Plain paper : Quality mode) 360 dpi x 720 dpi : Approx. 3.1 mins (Coated media : Fast mode) 720 dpi x 720 dpi : Approx. 3.8 mins (Coated media : Quality mode)

1440 dpi x 720 dpi : Approx. 5.4 mins (Photo mode)

PRINTER DRIVER Windows 98 / ME / 2000 / XP, Macintosh OSX 10.2 or later, Macintosh OS 9.1 or later

PAPER INPUT CAPABILITY

**ROLL MEDIA** Single roll (1roll < 150mm / Outside diameter)

Media width 203.2mm ~ 431.8mm (8" ~ 17") Minimum

Media length 279mm

Media thickness 0.08mm ~ 0.50mm

CUT SHEET High capacity paper tray with automatic sheet feed (up to 250 pcs of plain paper) Manual Insertion feeder for media up to 1.5mm

Media width size A4/LTR ~ A2/C, (210mm~431.8mm)

Media length 279mm ~ 610mm

Media thickness 0.08mm ~ 1.50mm

PAPER OUTPUT CAPABILITY Auto media cutter

**MEDIA DIMENSION** Roll: Width 203.2 ~ 432mm (8"~17"), A4~A2+

**PRINTING AREA (WIDTH)** Max. 432mm (Borderless Printing width: 8"(\*1), 10", 12", 14", 16", 17",

210mm, 257mm, 297mm, 300mm, 329mm, 400mm,

420mm(\*1))

1 8" & 420mm requires spacer.

**PRINT MARGINS** 

**ROLL MEDIA** 4 modes available;

mode 1: 3mm on all edges (top, sides, bottom), 2: 15mm (top and bottom), 3mm (sides), mode mode 3: 15mm (top, sides, bottom), mode 4: 25mm (top and bottom) 3mm (side)

SHEET MEDIA 2 modes available;

mode 1: 3mm (top, sides, bottom),

mode 2: 3mm (top and sides) 14mm (bottom)

**ROLL DIMENSION** Core diameter 2" or 3", Max. Outside Diameter ø 150mm

**MEMORY** 64MB **LANGUAGES** ESC/P2 Raster

**INTERFACES (STANDARD)** USB 2.0 (Hi-Speed), IEEE 1394 FireWire

Expansion Slot for optional Type B Ethernet 10/100 Base interface card

**VOLTAGE/ CURRENT/ FREQUENCY** 220 ~ 240V

**POWER CONSUMPTION** 

PRINTING 52W or less **STANDBY** 5W or less **POWEROFF** 1W or less

DIMENSIONS 848 (W) mm x 765 (D) mm x 354 (H) mm (Paper Tray Storage Min. Size),

848 (W) mm x 1105 (D) mm x 354 (H) mm (Paper Tray Expand Max. Size)

WEIGHT Approx. 39.0kg (excluding lnk and Media)

**UTILITY SOFTWARE** Epson LFP Remote Panel

WARRANTY One year. For more information on warranty coverage, please refer to

www.epson.com.sg

Dealer's Stamp



For enquiries, contact your nearest EPSON sales representatives:

INDIA - (91) 80-30515000, Toll-free Number - 1600 440011 INDONESIA - (62) 21-572-3161 MALAYSIA - (60) 3-562-88288 PHILIPPINES - (632) 813-6567 SINGAPORE - (65) 6337-7911, (65) 6586-3111 THAILAND / INDOCHINA - (662) 670-0680



## **SUPPLIES** -**Epson UltraChrome Ink**

T543200 Cyan T543300 Magenta T543400 Yellow T543800 Matte Black

T544200 Cyan T544300 Magenta T544400 Yellow T544800 Matte Black

C12C890191 Maintenance Tank C12C815291 Auto Cutter Spare Blade



be registered in certain jurisdictions

"EPSON ESC/P2 stands for EPSON standard code for printers Level 2. This second generation printer control language supports scalable fonts as well as enhanced graphics capability. It also provides complete backwards compatibility with EPSON's ESC/P, the standard printer language for dot matrix printing.

EPSON is the registered trademark of SEIKO EPSON CORPORATION. EPSON ESC/P2 is a trademark of SEIKO EPSON CORPORATION. PostScript is a trademark of Adobe Systems Incorporated or its subs

All other product names and other company names used herein are for identification purpose only and may be the trademarks or registered tratherir respective owners.

EPSON disclaims any and all rights in those marks.















www.epson.com.sg