

PRINT METHOD		9-pin, serial impact dot matrix
PRINT	FONT	7 x 9/9 x 9
	COLUMN CAPACITY (COLUMNS)	40/42 or 33/35 (3 half dots/ 2 half dots space)
	CHARACTER SIZE (MM)	1.2 (W) x 3.1(H)/1.6 (W) x3.1(H)
	CHARACTER SET	95 Alphanumeric, 32 International, 128 x 8 Graphic
	CHARACTERS PER INCH	16 or 17.8 CPI/13.3 or 14.5 CPI
INTERFACES		RS-232/Bi-directional parallel /RS-485 (dealer option)
DATA BUFFER		4K bytes or 45 bytes
PRINT SPEED		Approx 3.5 LPS (at 40 columns, 16 CPI) Approx 6.4 LPS (at 16 columns, 16 CPI)
PAPER	DIMENSIONS (MM)	Receipt: 76.0± 0.5 (W) x dia. 83.0
	THICKNESS (MM)	Receipt: 0.06 to 0.085 (total thickness 0.2mm or less) Validation: 0.09 to 0.12 (total thickness: 0.09 to 0.31, including thickness or roll paper)
COPY CAPABILITY		One original and two copies
INKED RIBBON		ERC-38 (purple, black)
RIBBON LIFE		Purple: 4 x 10 ⁶ characters, Black: 3 x 10 ⁶ characters
POWER		AC adapter (included)
POWER CONSUMPTION		Approx. 43W
D.K.D FUNCTION		2 drivers
RELIABILITY		MTBF: 18 x 10 ⁴ hours MCBF: 49 x 10 ⁶ lines
OVERALL DIMENSIONS		164 (W) x 240 (D) x 136(H)
WEIGHT		2.3kg
EMI STANDARD		FCC class A
POWER SUPPLY		Exclusive AC adapter (included)
SAFETY STANDARDS		UL/C-UL/TÜV