



## technical data

HP's advanced versatile colour printer with high speed, professional photo-quality and optional 6-ink photo printing capability

### professional photo-quality

- get best photo-quality with HP PhotoREt 3 colour layering technology — more colour shades for incredibly realistic images
- up to 4800 optimised dpi in colour\* and rich black text
- optional 6-ink colour printing with HP PhotoREt 4 colour layering technology offers you grain-free, stunning photographic images
- print longer lasting photos with specially formulated hp fade-resistant inks and photo papers

### performance


- prints up to 17 ppm in black and 12 ppm in colour
- networkable with optional hp jetdirect wired and wireless print servers

### innovative features

- easily print screen captures using the print-screen button on your computer keyboard
- borderless 4" x 6" photo printing on hp colourfast photo paper
- ink backup printing mode completes your print job even if one cartridge runs out of ink
- automatic paper-type sensor detects paper type and delivers optimum print performance
- optional automatic two-sided printing saves time and money

\* up to 4800 x 1200 optimised dpi colour printing on hp colourfast photo paper and 1200 x 1200 input dpi

# print confidence



## **hp** deskjet 5550

input dpi black: up to 1200 x 1200 dpi rendered blo document type black text mixed text/colour graphics full-page colour (photo paper) full-page colour (photo paper) full-page colour (photo paper)	fast photo pa ck text on inkj					
4800 x 1200 optimised dpi using hp colou input dpi <b>black:</b> up to 1200 x 1200 dpi rendered bla <b>document type</b> fast draft black text mixed text/colour graphics full-page colour (photo paper) full-page colour (photo paper) 95sec	fast photo pa ck text on inkj					
document type         fast draft           black text         17ppm           mixed text/colour graphics         12ppm           full-page colour (plain paper)         20sec           full-page colour (photo paper)         95sec		4800 x 1200 optimised dpi using hp colourfast photo paper and 1200 x 1200				
mixed text/colour graphics 12ppm full-page colour (plain paper) 20sec full-page colour (photo paper) 95sec	everyday	normal	best			
full-page colour (plain paper) 20sec full-page colour (photo paper) 95sec	8ppm 6ppm	6ppm 4ppm	1.7ppm 1.7ppm			
	36sec	65sec	250sec			
4" x 6" colour photo 45sec 80sec 90sec 115*/310**s * with PhotoREt; ** with 4800 x 1200 optimised dpi						
paper: plain, inkjet, photo, glossy; A4 210 279 mm; legal 216 x 356 mm; executive 18 banner: letter 216 x 279 mm; A4 210 x 29 envelopes: U.S. No.10 105 x 241 mm; A2 DL 110 x 220 mm; C6 114 x 162 mm transparencies: A4 210 x 297 mm; letter 2' labels: A4 210 x 297 mm; letter 216 x 279 index cards: 76 x 127 mm; 102 x 152 mm; Japanese Hagaki Postcard 100 x 148 mm; photo (with tear-off tab): 102 x 152 mm	< 297 mm; A5 34 x 267 mm; 7 mm invitation 111 6 x 279 mm mm 127 x 203 mr L-size card 89	B5-JIS 182 x 146 mm n; A6 card	2 x 257 mm 1; 105 x 148.5 mm;			
letter paper: 60 to 90 g/m²; legal paper: 7	5 to 90 g/m²;					
	20 sheets; <b>en</b>	velopes: up	o to 15;			
cards: up to 40; greeting cards: up	o to 5; <b>transpo</b>	arencies: up				
photo paper: up to 25	eller of A4-size	e sneeis);				
		to 25;				
	p 10 20					
	a madula: 15	6 mm v 15	6 mm v 295 mm			
96 Mhz						
8 MB built-in RAM						
Universal Serial Bus 2.0 full speed (PC and I Centronics)	Macintosh™) c	and paralle	l (IEEE 1284			
4 built-in bitmap font families: CG Times, Univers, Courier, Letter Gothic						
printing			maximum average			
		ng				
storage temperature: -40° to 70°C						
	d, 5.3 B(A);					
Windows XP Home and Professional: Pentiu						
Mac OS X: 128MB RAM	-, 021110 1.419	•				
Mac OS 8.6 – 9.x: 64MB RAM						
Microsoft Windows (NT® 4.0, XP Home and Professional, ME, 2000 Professional, 98 and 95); Mac OS X, 8.6 – 9.x						
		00				
Windows XF Home and Professional, 2000 Professional, 98 and 95 (ICF/IF, IPX/SPX) Windows NT® 4.0 and later (TCP/IP, IPX/SPX, DLC/LLC)						
Mac OS 8.6, 9, X and later (EtherTalk) Novell NetWare v3.11, 3.12.4.x, 5.0 (IPX/S		'SPX); NDP	s (TCP/IP, IPX/SPX)			
	175×1·					
Windows XP Home and Professional, ME, 20	00 Professiona	l, 98 and 9	95 (TCP/IP, IPX/SPX)			
ter and the termination	h d	enets in New Tanting				
			-			
	<ul> <li>279 mm; legal 216 x 356 mm; executive 18 banner: letter 216 x 279 mm; A4 210 x 29 envelopes: U.S. No.10 105 x 241 mm; A2 DL 110 x 220 mm; C6 114 x 162 mm transparencies: A4 210 x 297 mm; letter 216 x 279 index cards: 76 x 127 mm; 102 x 152 mm; Japanese Hagaki Postcard 100 x 148 mm; Japanese Hagaki Postcard 100 x 148 mm; photo (with tear-off tab): 102 x 152 mm; custom size: width 77 to 215 mm; length 12</li> <li>letter paper: 60 to 90 g/m²; legal paper: 77 banner paper: 60 to 90 g/m²; legal paper: 77 cards: up to 200 g/m²; levelopes: 7 cards: up to 200 g/m²; photo: 240 g/m²</li> <li>input: sheets: up to 100; banners: up to cards: up to 40; greeting cards: up labels: up to 20 sheets (use only le photo paper: up to 25</li> <li>output: sheets: up to 50; envelopes: up to 25; labels: u</li> <li>3,000 pages per month</li> <li>without optional automatic two-sided printing mith optional automatic two-sided printing mithout optiona</li></ul>	<ul> <li>279 mm; legal 216 x 356 mm; executive 184 x 267 mm; banner: letter 216 x 279 mm; A4 210 x 297 mm</li> <li>envelopes: U.S. No. 10 105 x 241 mm; A2 invitation 111 DL 110 x 220 mm; C6 114 x 162 mm</li> <li>transparencies: A4 210 x 297 mm; letter 216 x 279 mm</li> <li>labels: A4 210 x 297 mm; letter 216 x 279 mm</li> <li>labels: A4 210 x 297 mm; letter 216 x 279 mm</li> <li>index cards: 76 x 127 mm; 102 x 152 mm; 127 x 203 mr</li> <li>Japanese Hagaki Postcard 100 x 148 mm; Lsize card 89 photo (with tear-off tab): 102 x 152 mm</li> <li>custom size: width 77 to 215 mm; length 127 to 355 mm</li> <li>letter paper: 60 to 90 g/m²; legal paper: 75 to 90 g/m²; cards: up to 200 g/m²; photo: 240 g/m²</li> <li>input: sheets: up to 100; banners: up to 20 sheets; em cards: up to 200 g/m²; photo: 240 g/m²</li> <li>input: sheets: up to 100; banners: up to 20 sheets; em cards: up to 40; greeting cards: up to 5; transpt labels: up to 20 sheets (use only letter or A4-size photo paper: up to 25</li> <li>output: sheets: up to 50; envelopes: up to 10; cards: up transparencies: up to 25; labels: up to 20</li> <li>3,000 pages per month</li> <li>without optional automatic two-sided printing module: 5.8 kg</li> <li>96 Mhz</li> <li>8 MB built-in RAM</li> <li>Universal Serial Bus 2.0 full speed (PC and Macintosh™) of Centronics)</li> <li>HP PCL level 3 enhanced</li> <li>4 built-in bitmap font families: CG Times, Univers, Courier, power modules: input voltage 100 – 240 VAC ± 10%, 50</li> <li>2 watts maximum when off; 4 watts minimum non-printing printing</li> <li>recommended: 15° to 35°C, 20 to 80% RH non-condensing storage temperature: -40° to 70°C noise levels per ISO 9296: sound power twAd, 5.3 B(A); sound pressure LpAm, 40 dB(A) (best mode)</li> <li>CD-ROM drive or Internet access required</li> <li>Windows XP Home and Professional, Pentium® 133M Windows ME, 98 and 95: Pentium® 150Mhz; 32MB RAM Mac OS 8.6 – 9.x: 64MB RAM</li> <li>Microsoft Windows (NT® 4.0, XP Home and Professional, and 95); Mac OS X, 8.6 – 9.x</li> <li>with enha</li></ul>	<ul> <li>envelopes: U.S. No.10 105 x 241 mm; A2 invitation 111 x 146 mm DL 110 x 220 mm; C6 114 x 162 mm Iransparencies: A4 210 x 297 mm; letter 216 x 279 mm Index cards: 76 x 127 mm; 102 x 152 mm; 127 x 203 mm; A6 card Japanese Hagaki Postcard 100 x 148 mm; Leize card 89 x 127 mm photo (with tear-off tab): 102 x 152 mm custom size: width 77 to 215 mm; length 127 to 355 mm</li> <li>letter paper: 60 to 90 g/m<sup>2</sup>; legal paper: 75 to 90 g/m<sup>2</sup>; banner paper: 60 to 90 g/m<sup>2</sup>; nevelopes: 75 to 90 g/m<sup>2</sup>; cards: up to 200 g/m<sup>2</sup>; photo: 240 g/m<sup>2</sup></li> <li>input: sheets: up to 100; banners: up to 20 sheets; envelopes: up cards: up to 200 g/m<sup>2</sup>; nevelopes: up to 20 sheets; envelopes: up inbels: up to 50; envelopes: up to 10; cards: up to 25; transparencies: up to 55; tabels: up to 20</li> <li>output: sheets: up to 50; envelopes: up to 10; cards: up to 25; with optional automatic two-sided printing module: 456 mm x 155 with optional automatic two-sided printing module: 5.3 kg</li> <li>96 Mhz</li> <li>8 MB built-in RAM</li> <li>Universal Serial Bus 2.0 full speed (PC and Macintosh<sup>TM</sup>) and paralle Centronics)</li> <li>HP PCL level 3 enhanced</li> <li>4 built-in bitmap font families: CG Times, Univers, Courier, Letter Got power modules: input voltage 100 – 240 VAC ± 10%, 50/60 Hz ± 2 watts maximum when off; 4 watts minimum non-printing; 30 watts printing</li> <li>recommended: 15° to 35°C, 20 to 80% RH non-condensing maximum: 5° to 40°C, 15 to 80% RH non-condensing maximum: 5° to 40°C, 15 to 80% RH non-condensing maximum: 5° to 40°C, 15 to 80% RH non-condensing</li> <li>sound pressure LpAm, 40 dB(A) (best mode)</li> <li>CD-ROM drive or Internet access required</li> <li>Windows XP Home and Professional: Pentium<sup>®</sup> 133Mhz; 64ME</li> <li>Windows XP Home and Professional, 2000 Professional, ME, 2000 and 95]; Mac OS X, 8.6 – 9.x</li> <li>with enhanced Ethernet adapter (hp jedirect 380x):</li> <li>windows NT® 4.0 and later (TCP/IP, IPX/SPX; NDC/(LC)</li> <li>Mac OS X, 6.6 – 9.x</li> <li>windows NT® 4.0 and later (TCP/IP, IPX/</li></ul>			

### ordering information

number C6487C	description hp deskjet 5550 (includes removable paper tray; black print cartridge; colour print cartridge; power supply; power cord; Windows and Mac reference guides; Windows and Mac setup posters; printer software for PC and Mac on CD; hp photo paper sampler pack)			
C6656AA C6657AA C6658AA	supplies hp 56 black inkjet print cartridge hp 57 tri-colour inkjet print cartridge hp 58 photo inkjet print cartridge			
Q1951A Q1952A	<b>hp colourfast photo paper, glossy</b> A4-size, 20 sheets 4R-size, 20 sheets			
Z4269A	<b>hp flip magic! photo paper pack<sup>†</sup></b> 4R-size, 12 sheets, 4 magic lenses			
C6765A	<b>hp photo paper, glossy</b> A4-size, 20 sheets			
C7006A	<b>hp everyday photo paper, semi-gloss</b> A4-size, 25 sheets			
C6065A	<b>hp iron-on transfers</b> A4-size, 10 sheets			
C6829A	<b>hp textured greeting cards</b> <sup>†</sup> A4-size, 20 sheets, 20 envelopes			
Q1936A	<b>hp premium inkjet paper</b> A4-size, 200 sheets			
C8955A	<b>accessory</b> hp automatic two-sided printing module			
	external print servers			
J3258B	hp jetdirect 170x			
J6035A	hp jetdirect 175x			
J6061A	hp jetdirect 380x			
<sup>†</sup> Available in selected Asia Pacific countries only.				
To order HP supplies and accessories, contact your local HP sales office or nearest HP authorised dealer.				
Hewlett-Packard offices				
Australia	: ACN 004 394 763			
Hong Kong	: (852) 2599 7066			
India	: (91) 9628 123123			

nemen raciana on	i cc			
Australia	:	ACN 004 394 763		
Hong Kong	:	(852) 2599 7066		
India	:	(91) 9628 123123		
Indonesia	:	(62-21) 579 00323		
Korea	:	(82-2) 3270 0720		
Malaysia	:	(60-3) 2698 1111		
New Zealand	:	(0800) 733 547		
Philippines	:	(63-2) 636 9888		
PRC	:	(86) 800 820 2255		
Singapore	:	(65) 6272 1788		
Taiwan	:	(886-2) 2717 0055		
Thailand	:	(66-2) 353 9500		
Vietnam	:	(848) 823 6215		
Bangladesh, Brunei, Cambodia, Pakistan and				

Sri Lanka : Fax (65) 6275 6707

dealer's stamp

#### hp customer care

One-year limited warranty; optional HP SupportPack for 3 years from purchase date; 24-hour electronic support available free at **www.hp.com/go/support** For specific warranty details, please check with your local country reseller.

All brand and product names are trademarks of their respective companies. Technical information in this

For more information, visit us at http://www.hp.com/apac/homeandoffice





<mark>an Ut</mark>

full-page colour

and graphics The above thumbnail images are approximate representations of document types.

colour mixed text

black text

<sup>†</sup> Approximate figures. Exact speed will vary depending on the system configuration, software program and document complexity.

4" x 6" colour photo

document is subject to change without notice. © Hewlett-Packard Company 2002

© Hewlett-Packard Company 2002 Printed in Singapore 6/2002 P/N: 5981-1567EEP