









Your digital scanning centre for fast, true-to-life results.



HP Scanjet 4070

Photosmart Scanner



The HP Scanjet 4070 is your one-stop digital scanning centre. It features automatic photo enhancement and optimising functions at the touch of a button. Now, you can not only scan photos easily, but also convert documents and books efficiently into digital files that are easy to store and share.

One-stop photo scanning

Scan photos, slides and negatives quickly and effortlessly. The built-in HP photo door holds up to 12 standard-size photos or four 35mm slides or film negative frames in an optimised zone. You can easily convert these traditional photo formats into digital files for enhancing, printing, sharing and storing.

True-to-life images

Scan at 2400 dpi optical resolution and 48-bit colour for digital photo files with a high level of sharpness and clarity. The HP Scanjet 4070 allows you to easily optimise image quality so you can produce impressive photo prints.

Restore and enhance faded photos

Bring faded memories back to life at a touch of a button! Simply scan your faded photos and HP Image Zone's photo-correction function automatically restores colours and shades to your pictures, giving you brilliant images once again.

Scan and share effortlessly

Now, you can share photos easily with HP Instant Share. This user-friendly software lets you send image-rich emails to friends and family without the usual large file attachments.



scan photos, slides and negatives.





With 2400 dpi optical resolution, you ge visibly more outstanding image quality



Restore old photos to their original brilliance.









HP Scanjet 4070 Photosmart Scanner Superior scans at a touch

Scannor hano	Flatbed
Scanner type	
Input modes	Four-button front panel: Scan picture, Scan slides or negatives, Scan document, Copy; HP Image Zone software; Transparent Materials Adapter (TMA) user application via TWAIN
Additional features	Integrated Transparent Materials Adapter (TMA) in scanner lid; HP dual CCD technology; Hi-Speed USB-compatible with USB 2.0 specifications; HP Image Zone software; HP photo door
Speed	Preview speed: as little as 10 seconds Task speed: as little as 25 seconds – 4 x 6 inch photo to Microsoft® Word as little as 35 seconds – OCR full page as little as 22 seconds – 4 x 6 inch photo to email
Resolution	2400 dpi optical resolution 2400 x 2400 dpi hardware resolution up to 999,999 dpi enhanced resolution*
Imaging technology	Dual CCD
Bit depth	48-bit colour
Scaling	10 to 2000% in 1% increments
Maximum document size	216 mm x 297 mm (8.5 x 11.7 inches)
Interface and operating system requirements	Hi-Speed USB-compatible with USB 2.0 specifications OS Support: Microsoft® Windows® [98, 98 SE, Me, 2000, XP (Professional and Home Editions)]; Mac OS X 10.1.5, 10.2,10.3 or higher
Dimensions	298 x 472 x 90 mm
Weight	3.29 kg
Minimum system requirements	For PC: USB-compatible PC with Microsoft Windows [98, 98 SE, Me, 2000, XP (Professional and Home Editions)] with Intel Pentium III 500 MHz, Celeron, or compatible processor; 128 MB RAM; 500 MB disk space; Microsoft Windows Internet Explorer 5.01 SP2 or later; SVGA monitor (800 x 600, 16-bit colour); CD-ROM drive; USB port
	For Mac: USB-compatible Macintosh® computer with Mac OS X 10.1.5, 10.2, 10.3 or higher; 128 MB RAM; 240 MB disk space; SVGA monitor (800 x 600 16-bit colour); CD-ROM drive; USB port
Contents	 HP Scanjet 4070 Photosmart Scanner with HP photo door [including built-in Transparent Materials Adapter (TMA)] Hi-Speed USB cable—compatible with USB 2.0 specifications Power supply/ power cord (where applicable) User's manual Set-up poster Warranty statement CD-ROM with software for Microsoft Windows and Macintosh: HP Image Zone software with HP Instant Share Integrated I.R.I.S. ReadIris OCR (for Microsoft Windows only) ReadIris Pro 9 (for Macintosh only)
Multiple formats	For PC : TIFF, TIFF (multi-page), TIFF compressed, Bitmap, DCX, PCS, JPEG, GIF, FlashPix, Plain Text, PDF, HTML, Rich Text
	For Mac : TIFF, TIFF (multi-page), TIFF compressed, PICT, JPEG, GIF, FlashPix, Plain Text, PDF, HTML, Rich Text
Operating environments	Operating temperature range: 10 to 35°C Operating humidity range: 15 to 85% RH Storage temperature range: -40 to 70°C Storage humidity range: 0 to 90% RH
Power	Universal AC adapter: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/-3Hz) input (according to configuration), 12-VDC, 1.25-amp output, Energy Star™ complian
Regulatory compliance information	Safety EU (ICE 60950 third edition compliant; third party Safety Certification), North America (nationally-recognised testing laboratories), Poland (PCBC), Russia (GOST)

Ordering information
Number
Description
Number
HP Scanje

Hewlett-Packard offices







^{*} Maximum dpi is limited by available computer memory, disk space and other system factors.









Composite



Electromagnetic compatibilityEU (CE certification of conformity), North America (FCC), Australia (SMA), New Zealand (SMA), Russia (GOST), Korea (MIC), Taiwan (BSMI)